

[www.gmcair.co.uk](http://www.gmcair.co.uk)

# GECO

*/ ECONOMICAL TYPE EXHAUST FAN*



6 models are produced as standard with air flow ranging 1,000 to 15,000 m<sup>3</sup>/h.

- Economical solution for exhaust and ventilation operations
- Aluminum Profile Frame
- Double-wall panel, rock wool-insulated (in thickness of 40mm and density of 50 kg/m<sup>3</sup>)
- Centrifugal radial type fan, double suction, belt-pulley driven.
- Electro Static Kiln-Dried Paint resistant against external weather conditions
- Designed in minimum sizes, not occupying much space,
- Operates at very low sound levels,
- Delivery in very short time.



MODELS	Outer dimension			Ducting connection dimensions				Air Flow Rate (m <sup>3</sup> /h)	Static Pressure (Pa)	Motor Power (kW) (3 x 380V x 50Hz)
	B (mm)	H (mm)	L (mm)	a (mm)	b (mm)	c (mm)	d (mm)			
15-25610	610	610	610	300	350	210	230	1,500 - 2,500	250 - 400	0,55 - 1,1
25-35	710	710	710	350	450	260	300	2,501 - 4,000	400 - 600	0,75 - 1,5
35-45	810	810	810	300	750	290	330	3,501 - 5,000	400 - 600	0,75 - 2,2
45-65	810	810	810	400	750	340	400	4,501 - 7,000	400 - 600	1,1 - 2,2
65-100	910	910	910	500	850	405	470	6,500 - 10,000	400 - 600	1,5 - 3,0
100-150	1060	1060	1260	600	1000	480	560	10,000 - 15,000	400 - 600	3,0 - 5,5

